



## Falkenoil ATF CVT

### Description/Application/Properties

**Falkenoil ATF CVT** is an Automatic Transmission Fluid which is made by multi vehicle anti-shudder additive technology optimized for passenger car applications.

**Falkenoil ATF CVT** is used in an extensive range of European and American passenger car service fill applications, it also can be used in commercial vehicle applications and power steering.

**Falkenoil ATF CVT** affords following benefits:

- Exceptional oxidation behavior
- Anti-shudder durability
- smoother shifts over a long period of time
- excellent anti-rust properties
- low foaming tendency

### Specification/Recommendation

- Aisin Warner JWS 3309
- Allison C-4, TES-295, TES-389
- BMW/Mini P/N 81 22 9 400 272/275
- BMW/Mini P/N 81 22 9 407 858/859
- BMW/Mini P/N 83 22 0 024 249/359
- BMW/Mini P/N 83 22 0 026 922 (BMW 7045 E)
- BMW/Mini P/N 83 22 0 402 413
- BMW/Mini P/N 83 22 0 403 248/249
- BMW/Mini P/N 83 22 7 542 290
- BMW/Mini P/N 83 22 9 407 765 (BMW LA 2634)
- Chrysler/Dodge/Jeep AS68RC ATF
- Chrysler/Dodge/Jeep ATF+2/ATF+3/ATF+4
- Chrysler/Dodge/Jeep SP-III
- Daimler/Mercedes MB 236.3, 236.5, 236.6, 236.7
- FORD WSS-M2C919-E (Mercon V)
- FORD/Lincoln/Mercury P/N XT-2-QDX [M]
- FORD/Lincoln/Mercury P/N XT-2-QSM [Syn]
- FORD/Lincoln/Mercury P/N XT-5-QM or -DM [V]
- FORD/Lincoln/Mercury P/N XT-8-QAW [Premium]
- FORD/Lincoln/Mercury P/N XT-9-QMM5 [FNR5]
- FORD/Lincoln/Mercury WSS-M2C922-A1
- GM DEXRON II / II-D / II-E / III-G / III-H
- GM/GMC/Opel/Saturn P/N 19 40 700/767
- GM/GMC/Opel/Saturn P/N 21005966 (transaxle)
- GM/GMC/Opel/Saturn P/N 22717466
- GM/GMC/Opel/Saturn P/N 88900925/9986195
- GM/GMC/Opel/Saturn T-IV, Type A Suffix A
- Jaguar JLM 20238 / 20292 / 21044 / K17
- Jaguar WSS-M2C922-A1
- Land Rover Texaco ETL-7045E
- MAN 339 A
- MB 236.8, 236.9, 236.10, 236.91
- Mercon V
- Mobil ATF 3309
- Porsche P/N 000 043 204 41
- Porsche P/N 000 043 205 09
- Porsche P/N 999 917 547 00 (A2)
- PSA Peugeot Citroen P/N Z 000169756
- Renault Matic D2
- Renk Genuine Oil
- Saab 3309 – T-IV
- Shell 3403-M115, LA 2634
- Texaco ETL 7045E / 8072B, N402
- Voith H55.6335.XX
- Voith Svc Bltn # 013 / 118
- Volvo P/N 1161521
- Volvo P/N 1161540 / 1161640
- Volvo P/N 1273,41
- VW/Audi G 052 025 A2, G 052 055
- VW/Audi G 052 162 (A1, A2)
- VW/Audi G 052 990 (A2), G 055 025 (A2)
- VW/Audi US 000 162
- ZF TE-ML 11A / 11B



<b>Falkenoil ATF CVT</b>	<b>unit</b>	<b>value</b>	<b>method</b>
Density at 15°C	kg/m <sup>3</sup>	850	DIN 51 757
Viscosity at 40°C	mm <sup>2</sup> /s	38,2	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	7,0	DIN 51 562
Viscosity index		150	DIN ISO 2909
Pourpoint	°C	-45	DIN ISO 3016
Flash point COC	°C	228	DIN ISO 2592