



Falkenoil ATF DX VI

Description/Application/Properties

Automatic Transmission Fluid which is made by multi-vehicle anti-shudder additive technology optimized for passenger car applications, used in an extensive range of European and American passenger car service fill applications, it also can be used in commercial vehicle applications and power steering.

- Exceptional oxidation behavior
- Anti-shudder durability
- smoother shifts over a long period of time
- excellent anti-rust properties

Specification/Recommendation

DEXRON VI	Hyundai/Kia P/N 040000C90SG
Aisin Warner AW-1	Hyundai/Kia SP-IV / SPH-IV
Aisin Warner AW F8FXX	Jaguar Fluid 8432
Aisin Warner JWS 3324	JASO M315, Class 1A
Bentley P/N PY112995PA	Land Rover P/N TYK500050, LR0022460
BMW/Mini P/N 83 22 0 142 516	Maserati P/N 231603
BMW/Mini P/N 83 22 0 397 114	Mazda FW 6A EL, FW 6AX EL
BMW/Mini P/N 83 22 2 163 514 (BMW 8072 B)	Mazda FZ
Chrysler/Dodge/Jeep P/N 05127382AA	Mercon LV
Chrysler/Dodge/Jeep P/N 68043742AA	Mitsubishi ATF-J3
Daimler / Mercedes MB 236.12, 236.14, 236.41	Mitsubishi SP-IV
FORD/Lincoln/Mercury P/N XT-10-QLV [LV]	Nissan/Infinity Matic-S
FORD/Lincoln/Mercury P/N XT-6-QSP or -DSP [SP]	Porsche P/N 000 043 304 00
GM/GMC/Opel/Saturn AW1	Saab P/N 93 165 147 - AW-1
GM/GMC/Opel/Saturn P/N 88863400, 88863401	Shell 3353, Shell 134, Shell 1375.4
Honda/Acura DW-1	Toyota/Lexus/Scion WS
Honda 082000-9017 (ATF Type 3.1)	VW/Audi G 052 533, G 055 005 (-A, A2)
Hyundai/Kia NWS-9638 T-5	VW/Audi G 055 540 (A2)VW/Audi US 000 162

Falkenoil ATF DX VI	unit	value	method
Density at 15°C	kg/m ³	841	DIN 51 757
Viscosity at 40°C	mm ² /s	27,1	DIN 51 562
Viscosity at 100°C	mm ² /s	5,6	DIN 51 562
Viscosity index		157	DIN ISO 2909
Pourpoint	°C	-45	DIN ISO 3016
Flashpoint	°C	226	DIN ISO 2592